The Healthy Home Experts®



Proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in "The Proof")

THE TECHNOLOGY

The AP500 is a compact unit that mounts directly into a standard wall outlet and uses advanced photocatalytic oxidation technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in "The Proof" section below).

THE PROOF

In extensive unaffiliated lab testing, our technology has been proven to significantly reduce the following contaminants and pathogens:

- SARS-CoV-2 RNA Virus
- H1N1 Influenza
- H5N8 Influenza
- Murine Norovirus
- PhiX-174
- · MS2 Bacteriophage
- MRSA
- E. coli
- · Salmonella enterica
- Legionella pneumophila
- · Clostridium difficile
- · Bacillus globigii

- · Erwinia herbicola
- · Listeria monocytogenes
- · Candida auris
- · Botrytis cinerea
- · Sclerotinia sclerotiorum
- · Aspergillus versicolor
- Aspergillus niger endospores
- Methicillin-resistant Staphylococcus epidermis
- Staphylococcus epidermidis

THE BENEFITS

The AP500 utilizes our proprietary technology to effectively treat indoor air and exposed surfaces, helping to reduce surface and airborne contaminants, allergens, and odors. A powerful, inconspicuous air purification system intended for use in small spaces.

- Disinfects surfaces and air, removes VOCs, smoke and odor
- · Removes allergy and asthma triggering contaminants
- Compact, natural air treatment system for up to 250 sq. ft.
- Plugs into standard 120 volt electrical outlet
- · Anti-theft mounting arrangement, no wiring required





SPECIFICATIONS

Product Information	00693 Model: A1028A This DOES NOT meet California requirements and can not be shipped in California.
Technology Included	Photocatalytic Oxidation
Electrical	Supply Voltage: 120V~, 60 Hz, .18 Amp, Power Consumption: 13 Watts
Mechanical	One control switch, on/off
Weight & Dimensions	2.9 lbs (1.3 kg) 6"W x 12"H x 4"D (15.24 cm W x 30 cm H x 10 cm D)
Recommended Maximum Coverage in a Contiguous Space*	Up to 250 sq. ft. (23m²) depending on occupant density and other factors¹. High density commercial not to exceed 100 sq. ft. (9m²). Not for use in medical or health care environments. *Depends on room occupancy and layout
Warranty	Limited 3 year warranty (Terms & Conditions apply)